



Atty Dkt. 213407.00010

PATENT APPLICATION

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
: Examiner:
MARTIN D. NATHANSON) V. Lesniewski
: Group Art Unit: 2155
Application No.: 10/014,889)
: Confirmation No.: 2385
Filed: December 14, 2001)
:
For: AUTOMOTIVE TELEMETRY PROTOCOL)

Mail Stop AMENDMENT
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

DECLARATION OF MARTIN NATHANSON
UNDER 37 CFR § 1.131

I, Martin Nathanson, having a post office address at 29 Southvale Drive, Toronto, Ontario, Canada, M4G 1G1, do hereby declare and say as follows:

1. I am the original and only inventor of the subject matter disclosed and claimed in the above-identified U.S. patent application. I have reviewed the subject application, the February 2, 2005 Official Action, and the Amendment being submitted concurrently herewith, in preparing this Declaration.

2. I conceived the subject matter of at least the inventions recited in independent Claims 1, 19 and 20 prior to the January 27, 1999 filing date of U.S. Provisional Application 60/117,487 identified on U.S. Patent No. 6,295,492 to Lang. Furthermore, I acted to diligently reduce to practice the subject matter of at least the inventions recited

3. Enclosed as Exhibit A are copies of disclosure materials describing the conceived inventions recited in independent Claims 1, 19 and 20. These materials were created prior to January 27, 1999, and establish that the invention was conceived prior to January 27, 1999. These materials also provide evidence that the invention was being diligently reduced to practice from the conception thereof up to at least January 27, 1999.

4. Exhibit A describes A method of collecting vehicle operation data from a vehicle for later transmission to a remote monitoring recipient in a manner to minimize the bandwidth requirements for the later transmission, comprising the steps of:

- providing a vehicle on-board computing device;
- providing a number of data acquisition modules, each to measure one or more operating characteristics of the vehicle, the operating characteristics corresponding to current values of a set of managed objects;
- interfacing the vehicle on-board computing device with each of the data acquisition modules;
- configuring the vehicle on-board computing device to:

a) form a diagnostic information base for receiving and storing values for each of the managed objects from each of the corresponding data acquisition modules;

b) assemble an event report based on information contained in the diagnostic information base; and

c) package the event report in a protocol data unit according to an SNMP-derived protocol. (See Claim 1.)

5. Exhibit A also describes A method of conveying vehicle operation data from a vehicle to a remote monitoring recipient, comprising the steps of:

- establishing a data link between the vehicle and the remote monitoring recipient;
- collecting vehicle operation data from data sources in the vehicle;
- packaging the vehicle operation data in a data packet using protocol derived from SNMP; and
- conveying the data packet over the data link, the protocol data unit being issued in response to a request by the remote monitoring recipient and containing both the request and requested values in the request and being encapsulated within a single message and in a single unfragmented network packet. (See Claim 19.)

6. Exhibit A also describes A computer implemented system for conveying vehicle operation data from a vehicle to a remote monitoring recipient, comprising:


- an vehicle on-board computing device in communication with a number of vehicle operation data sources in the vehicle;
- a wireless communications device for establishing a wireless data link with the vehicle on-board computing device and the remote monitoring recipient;

the vehicle on-board computing device being enabled to package the vehicle operation data in a data packet using protocol derived from SNMP for transmission to the remote monitoring recipient over the wireless data link. (See Claim 20.)

7. Therefore, it is evident that the present application claims inventions that were conceived of and being diligently reduced to practice prior to January 27, 1999.

8. I hereby declare that all statements made herein of our own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such wilful false statements may jeopardize the validity of the application or any patent issued thereon.


Martin Nathanson


August 8 2005
 Date

From: Martin Nathanson <martinn@smtp.Generation.NET>
To: TOR4.MCTET2(SHOWE)
Date: [REDACTED] 12:22pm

The only inventor to be named in the application is myself:

Martin Daniel Nathanson
5301 Cumberland Ave.
Montreal, Qc, Canada
H4V 2P1

Canadian citizen.

The patent is to be assigned to a company. If we need to identify the company immediately, then it will be Transcontech Corporation. which is my consulting company (federally chartered).

I noticed some typographic errors in the UOBD.DOC that I sent you so I am attaching a new version.

Please confirm that you have received my check and brochures.

Thanks.

From: Stuart Howe
To: SMTP("martinn@smtp.Generation.NET")
Date: [REDACTED]:48am
Subject: Patent Documentation -Reply

Martin:

We have conducted a brief review of the documents you sent and will get back to you when we have the other information you indicated was being sent. In the meantime, I need some information regarding full names, addresses and citizenships for all inventors and an indication whether the rights are going to be owned personally or be assigned to a company/third party. Please provide this information asap.

Have a great long-weekend. Regards.

From: Martin Nathanson <martinn@smtp.Generation.NET>
To: TOR4.MCTET2(SHOWE)
Date: [REDACTED]:28pm
Subject: Patent

Attached are three (3) background documents. They are in Microsoft Word 7 format. In case you have difficulty with this, I have also included ASCII text versions.

The first two refer to our Mobile Automotive Telemetry System (MATS), as developed for the heavy equipment market. By the way, in case you were not aware (as I was not) that when people in the industry use the term "automotive market", they specifically means passenger cars. This is what we are targeting for the patent.

(1) MATSDATA.DOC is basically a data sheet describing the hardware and software components of the system. I am mailing you a glossy product sheet with the retainer check.

(2) MATSDESC.DOC describes the essential characteristics of the system which should interest an OEM (truck manufacturer).

The third document was written last night and this morning and constitutes a initial draft of a technology description for the patent application, that I hope will allow you to orient yourself. Please note that I have not had any chance at all to talk to my partner who handled all the hardware and operating system software issues, so there is probably a lot more to follow on these subjects. He has extensive experience in studying patent documents and should be able to help me get very "focused".

Martin

uobd-test

Universal On-Board Diagnostic Server

The universal on-board diagnostic (U-OBd) server is a vehicular computer which provides remote access to on-board diagnostic data through a variety of communications channels. The U-OBd server maintains a database of automotive functions objects which record performance data and respond to requests for information from authorized clients.

Purpose

To provide universal, real-time, flexible accessibility to automotive on-board diagnostic (OBd) data and to ensure full Internet connectivity to any part of the vehicle, including a portable computing device.

Client/Server Architecture

The embedded software in the ETC is structured according to an object-oriented client-server model which allows all monitored automotive functions to appear as though they are local to the remote client device. Remote clients interface to an API (Application Programming Interface) which provides a well-defined set of function calls for the following capabilities:

- * Configuration of the U-OBd server to establish acceptable threshold values for each automotive function. When these thresholds are exceeded, the server creates alarm objects which stream and transmit themselves to the client.
- * Retrieval of automotive function data. The server can be requested to create and transmit reports for specific functions at user-defined intervals and for user-defined durations.
- * Registration of client processes to be notified when alarms and reports are received from the U-OBd server.

Process Architecture (This section is subject to modification)

The process architecture defines the active objects (threads or polled functions) running within the firmware embedded in the U-OBd server. The threads related to communications shall be detailed in a subsequent version of this document. The primary active object which is unique to the U-OBd server is the monitor object provides the interface to both the OBd-2 Diagnostic Protocol and the DSP module and assures a real-time flow of diagnostic information from these interfaces to client objects which have expressed their interest in this information.

Communications Architecture

Internet Telemetry

In order to provide a universal communications channels from any client to any mobile U-OBd server, the technology uses the Internet paradigm coupled with sub-network drivers to interface to whichever packet-switched mobile data communications networks for which the U-OBd is equipped with hardware access devices. (See Sub-network Datalinks).

The embedded communications software therefore incorporates an object-oriented implementation of the complete Internet protocol suite, including IP(version 4), TCP, UDP, IGMP, ICMP, SNMP and PPP.

IP Defines the packet switching framework for datagrams (packets) over the Internet. IP determines whether a datagram should be forwarded (routed) from one computer to another, given the destination address encapsulated in the datagram, or has reached its final destination.

TCP Transport Control Protocol. Provides reliable data delivery between two end points (nodes in the Internet)

UDP User Datagram Protocol. Defines framework for (unreliable)delivery of individual IP datagrams

IGMP Internet Group Message Protocol. Defines abstract method for multicast or broadcast from a single origin to multiple destinations. Useful when the same message needs to be sent to an entire fleet. It is therefore desirable to avoid the cost of re-transmission of the same message to each and every mobile unit

This works only in the case where the underlying network technology supports this and provides an advantageous rate structure for group messaging. For instance, this is the case with Ericsson Mobitex.

ICMP Internet Control and Message Protocol. Defines a set of control and error messages. In particular, ICMP allows routers to report failures to reach destinations and indicate to the originator of the datagram, the reason for the failure. This is critical in networks with mobile nodes which frequently fall into and out of "reachability".

SNMP Simple Network Management Protocol. In conventional TCP/IP networks or the Internet, this provides for network administrators to have remote access to traffic statistics in routers and to remotely update address tables in routers. Examples of

applicability are where OE manufacturers or the management of a large end-user fleet want to add additional sites from which TCP connections, with (or SCADA services from) mobile units can be established. This means that the corporate computing network is expanding and the job of a network administrator is to ensure that the computers responsible for routing traffic are aware of the address of new sites in order to properly route new traffic destined for these site. SNMP is used to accomplish this. The on-board computer must therefore "speak" SNMP in order to be kept abreast of new entities in the corporate network with which it can communicate.

PPP Point-to-point protocol. Used for serial connections between permanent Internet nodes and temporary nodes which "live" on the Internet for the duration of the connection. Typically applies to the protocol between a personal computer and an Internet service provider over a telephone link. MATS uses this for connection between lap-tops or hand-held computers and the Engine Telemetry Computer, where the latter is the permanent Internet node.

Note that the IP implementation incorporates a Router object which, assisted by innovations introduced in the ICMP implementation, is capable of identifying the least-cost route to a specific mobile unit when that server interfaces to more than one mobile data network. Furthermore, the IP implementation is for version 4 whereas the Internet Engineering Task Force (IETF) has recently adopted a new version which provides more support for mobility and dynamic routing to mobile Internet nodes. Implementation of this new version shall be incorporated in a second generation of the U-OBD technology.

Sub-network DataLinks

The sub-network datalinks are the drivers for each specific packet-switched mobile data technology for which the U-OBD server has a network access device (radio modem). The datalinks currently supported are Mobitex (Ericsson) and ARDIS (Motorola). Support for the ORBCOMM system (low-earth orbit satellite, VHF, data-only) is pending.

InfraRed

The U-OBD server incorporates a full implementation of the IrDA (Infrared Data Association) specification. This is a complete protocol stack, including a datalink layer IrLAP (Link Access Protocol), a sub-network layer IrLMP (Link Multiplexing Protocol) and SNMP-like protocol called IAS (Information Access Service). Each of these has been implemented as an object -oriented class derived from a base class which is shared with some other entity within the communication system.

The use of the entire IrDA stack is the basis for enabling the wireless, universal connectivity in the garage as described in the following section. However, at the same time, the IrLAP implementation is also a means of provided a wireless datalink for a PPP connection between the U-OBD server and a IrDA-enabled hand-held or portable

computing device with Internet software. In this way the U-OBD server also acts as an mobile Internet router/service provider.

Data Acquisition Links

OBD-2 Diagnostic Protocol (This section is subject to extensive modification)

OBD-2 Diagnostic Protocol is an SAE (Society of Automotive Engineers) standard for data retrieval from vehicular electronic control modules (ECM's). In addition to providing access to performance data via remote telemetry, the U-OBD server also provides a wireless IR (InfraRed) solution to the problem of heterogeneous physical interfaces (connectors and electrical signals) between the ECM's and diagnostic tools of various manufacturers. By implementing the OBD-2 diagnostic protocol as a datalink between itself and the ECM, the U-OBD server can offer transparent services to the diagnostician (mechanic) using the information access service (IAS) protocol of the IrDA (Infrared Data Association) specification. This achieves the following:

- * eliminates the need for cabling connections with vehicular computers for uploading of information in the garage.
- * capitalizes on the expected widespread availability of new hand-held computing devices based on Microsoft's Windows CE (Computer Electronics) operating system. CE is a version of Windows specifically designed for these devices. Both the CE software and the devices comply with the IrDA specification for standardized datalinks between computers, laptops, handhelds, printers, modems and cellular phones via infrared serial ports integrated into the hardware.
- * by enabling vehicular computers to upload their accumulated diagnostic data to an IrDA-compliant PDA (personnel digital assistant), a wide variety of additional possibilities becomes apparent. Since the PDA's are so ubiquitous, many passenger car owners will own, and frequently carry with them, such devices. Furthermore, it will become more and more common for these devices to have integrated cellular phone modems or (packet radio modems) and to see them being used in conjunction with cellular phones. Therefore diagnostic information can be acquired by the car owner through the IR port in the PDA and transferred via modem to the garage, if required.

NMEA

Nation Marine Electronic Association is a protocol standard for exchange with a external GPS receiver. The NMEA is embedded in the U-OBD server in order to enable location services for a client as well as to attached location stamps to data reports and alarms.

Analog and Digital Signal Processing

The U-OBD server can be configured with a bank of analog and digital signal inputs for sensors not connected to an ECM. A digital signal processing (DSP) software module handles these inputs and relays them to the active monitor object.

Hardware

(See Product Description). After allocation of three(3) RS-232 ports to the GPS receiver, radio modem and a satellite transceiver or cellular modem, one port remains for user access through an infrared link. The ETC (Engine Telemetry Computer) therefore incorporates an IrDA-compliant IR adapter for the spare serial port.

Matsdata.txt

MOBILE AUTOMOTIVE TELEMETRY SYSTEM

Product Description

The primary features of the AMT Mobile Automotive Telemetry System are:

- * an on-board vehicular device which supports automotive sensor input and GPS
- * communications which is independent of the underlying radio network
- * Windows NT Base Station.

Hardware

Engine Telemetry Computer (ETC)

- * CPU
- * 16 analog input
- * 16 digital inputs
- * 2 RS-232 ports

These are for user applications such as dispatching messaging to terminals in the cab. The external device can communicate with the ETC using TCP/IP and PPP (point-to-point protocol) and can therefore be addressed in Internet fashion by the Base Station or any other device using the Base Station as an Internet Protocol router.

- * 2 RS-485 ports

These are to support the SAE (Society of Automotive Engineers) J1708 standard for data acquisition and control on board trucks and buses.

- * GPS receiver
- * Radio network access device

The ETC is designed to meet the harsh environmental, mechanical and electrical requirements of an automotive application.

- * -30 (C/ +60 (C operating temperature
- * designed for compliance with SAE (Society of Automotive Engineers) J1211 (recommended environmental practices for electronic equipment)
- * designed for compliance with SAE J1113 (conducted and radiated susceptibility)
- * 10,000 hrs MTBF

Base Station

- * Windows NT Computer

Software

Engine Telemetry Computer

The software in the ETC is an entirely object-oriented design and implemented in C++ . It consists of:

- * Intelligent digital signal processing module
- * SCADA (Supervisor Control and Data Acquisition) Server
- * TCP/IP protocol stack for wireless communications
- * Data privacy: where required, optional communications encryption is available (subject to export regulations).

Together, these software components allow for the following capabilities of the ETC:

- * can be remotely configured by the Base Station
- * can report automotive and operational events to the Base Station
- * can route wireless data traffic to and from other computing devices in the vehicle

Base Station

The Base Station software is an entirely object-oriented design and implemented in C++ . It consists of:

- * SCADA client
- * OODBS (object-oriented database system)
- * TCP/IP protocol stack for wireless and LAN communications

These software components allow the Base Station to act as a client with respect to the ETC's, The Base Station may :

- * remotely configure the ETC software
- * request and receive ETC reports in real-time
- * store ETC reports in the OODBS
- * display real-time graphic representation of automotive functions monitored by the ETC
- * alert third-party systems of ETC alarms using RPC's or Sockets.

**MOBILE AUTOMOTIVE
TELEMETRY SYSTEM**
Product Description

Mobile Automotive Telemetry System Executive Summary

The Mobile Automotive Telemetry System (MATS) is technology which grew out of the developers' experience with the application of mobile data communications to fleet operations. It was recognized that there is a need, common to all fleets, for real-time monitoring of all automotive functions which could enable preventive maintenance programs to be driven by alarm incidents from the field. Automotive telemetry, as it has been implemented, consists of an on-board vehicular computer which reports exception conditions to the maintenance garage and responds to any queries that a mechanic issues from a work station in the garage, even while the vehicle is on the road.

To achieve the communications link, MATS uses whatever mobile data facilities are most appropriate for the fleet in question, including public RF packet networks such as Ericsson's Mobitex or satellite systems such as ORBCOMM. The communications software architecture treats each of these as a physical "sub-network" according to the Internet model. (The prototype version of the ETC currently incorporates an access device - radio modem - for the Ericsson network). However, it is not simply a matter of following this model. MATS also incorporates an implementation of the Internet standards so that the on-board computer becomes Internet-addressable.

This means that packet-based Internet communications with the vehicle becomes possible for a wide variety of applications. In addition to the link between a fleet maintenance department and the vehicle, there is also the potential for the Original Equipment Manufacturer's product support staff to assist end-user customers with technical diagnoses or to validate dealer warranty claims through remote monitoring. Regulatory bodies responsible for commercial vehicle licensing and highway safety can carry out remote electronic inspections.

Furthermore, since there are many applications for mobile data exchange with the driver (eg. E-MAIL, dispatch, database query), the Engine Telemetry Computer (ETC) supports a PPP (point-to-point protocol) connection for portable or hand-held computing devices in the cab. This provides a TCP/IP communications platform to anywhere in the Internet in exactly the same fashion as does an Internet Service Provider (with the exception that the PPP link operates over a direct connection between the in-cab computer and the ETC instead of over a telephone line between the subscriber and the Internet Service Provider).

In order to provide for a comprehensive monitoring capability, the ETC has a bank of 16 A/D channels for sensor inputs, 16 digital (pulse) channels for discrete inputs (eg. tachometer, gear position, intrusion alarms) and RS-485 ports for interface to the SAE J-1708 data bus, in addition to the signal processing and J-1708 protocol software required to acquire various types of data. This hardware configuration is expandable to support both more inputs as well as discrete outputs for security applications.

From: Martin Nathanson <martinn@smtp.Generation.NET>
To: TOR4.MCTET2(SHOWE)
Date: [REDACTED] 1:39pm
Subject: Patent Documentation

I realize that the documentation I have sent to you is a little deficient in the "diagram department". Don't worry. This will be corrected soon.

Martin

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.